



SETUP SHEET



TRACK CONDITIONS			
Type :	<input checked="" type="checkbox"/> Carpet	<input type="checkbox"/> Asphalt	
Place :	<input checked="" type="checkbox"/> Indoor	<input type="checkbox"/> Outdoor	
Surface :	<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input type="checkbox"/> Bumpy
Size:	<input checked="" type="checkbox"/> Open	<input type="checkbox"/> Med.	<input type="checkbox"/> Tight
Traction:	<input checked="" type="checkbox"/> High	<input type="checkbox"/> Med.	<input type="checkbox"/> Low
Track Temp/Air Temp:	_____ / _____		
Note:	_____		

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: _____ 1°	<input type="checkbox"/> Ball Diff
Caster: _____ L2/R1,5°	<input type="checkbox"/> One Way
Camber: _____ 4°	<input checked="" type="checkbox"/> Solid Axle
Ride Height: _____ 5 mm	Anti-Roll Bar: ∅ _____ 1,5 mm
Down Stop: _____ 7 mm	

Shim: 1 mm

Shim: 2,5 mm

Shim: 3 mm

Shim: 3 mm

Shim: 0,5 mm

Shim: 1 mm

Shim: 1 mm

Shim: 1 mm

Diff. High Low

+0.75

0

-0.75

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff 1000 CPS wt
Toe Angle: _____ 3°	<input type="checkbox"/> Ball Diff
Camber: _____ L2/R1,5°	<input type="checkbox"/> Solid Axle
Ride Height: _____ 5,5 mm	
Down Stop: _____ 3 mm	Anti-Roll Bar: ∅ _____ 1,2 mm

Shim: 4 mm

Shim: 2 mm

Shim: 0 mm

Shim: 1,5 mm

Shim: 1,5 mm

Shim: 1,5 mm

Diff. High Low

+0.75

0

-0.75

STIFF SETTING	

ELECTRONICS
Servo: Futaba BLS
ESC: Orca
Battery: Orion

DRIVE RATIO
Spur 114 T
Pinion 24 T $\times 1.9 = 9.03$

MOTOR
Brand: Orca
Turns: 4,5
Timing: 0

TIRES
Insert: Handout
Wheel: Handout
Shore/deg: Handout
Compound: _____
Tire Temp: _____
Tire additive: LRP Carpet 2
Treated Area

ESC
Punch: 5
Initial Brake: 0
Drag Brake: 3%
<input checked="" type="checkbox"/> ESC Timing <input checked="" type="checkbox"/> Turbo Timing
ESC 9° Turbo 32°

FL FR RL RR

SHOCKS	
	Hole Size: F Kit _____ R Kit _____
	Holes In Piston: F Kit _____ R Kit _____
	Oil wt: F 550 _____ R 550 _____
	Springs: F 27 _____ R 25 _____
	Rebound: F 0 _____ R 0 _____
	Bladder Note: Kit _____
	Thread Length: F no Thread R no Thread

BODY	
	Body: LTC-R LW
	Wing Height: Limit
	Wing Position: Limit