



SETUP SHEET



TRACK CONDITIONS			
Type :	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	
Place :	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	
Surface :	<input type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input checked="" type="checkbox"/> Bumpy
Size:	<input type="checkbox"/> Open	<input type="checkbox"/> Med.	<input checked="" type="checkbox"/> Tight
Traction:	<input type="checkbox"/> High	<input type="checkbox"/> Med.	<input checked="" type="checkbox"/> Low
Track Temp/Air Temp:	_____ / _____ 28		
Note:	_____		

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: _____ 0°	<input type="checkbox"/> Ball Diff
Caster: _____ 4°	<input type="checkbox"/> One Way
Camber: _____ 1.5°	<input checked="" type="checkbox"/> Solid Axle
Ride Height: _____ 5 mm	Anti-Roll Bar: ∅ _____ 1.4 mm
Down Stop: _____ 6 mm	

Shim: 1 mm

Shim: _____ mm

Shim: 1.9 mm

Shim: 1.5 mm

Shim: 2 mm

Shim: 1 mm

Shim: 1 mm

Shim: _____ mm

Diff. High Low

+0.75

0

-0.75

REAR SUSPENSION	
Track Width: _____ mm	<input checked="" type="checkbox"/> Gear Diff _____ 1000 wt
Toe Angle: _____ 3	<input type="checkbox"/> Ball Diff
Camber: _____ 1	<input type="checkbox"/> Solid Axle
Ride Height: _____ 5 mm	
Down Stop: _____ 5 mm	Anti-Roll Bar: ∅ _____ 1.2 mm

Shim: 4 mm

Shim: _____ mm

Shim: _____ mm

Shim: 1.5 mm

Shim: 2 mm

Shim: 1 mm

Diff. High Low

+0.75

0

-0.75

STIFF SETTING	
<p>Upper Deck: <input checked="" type="radio"/> 2.0mm <input type="radio"/> 2.3mm <input type="radio"/> 2.5mm</p>	<p>Chassis: <input checked="" type="radio"/> 2.3mm <input type="radio"/> 2.5mm <input type="radio"/> 3.0mm</p>

ELECTRONICS
Servo: Savox 1251
ESC: HW V3
Battery: IP 6800

DRIVE RATIO
Spur 96 T
Pinion 40 T
X1.9 = 4.56

MOTOR
Brand: Thunder Power
Turns: 10.5
Timing: 40°

TIRES
Insert: _____
Wheel: _____
Shore/deg: Ride 36
Compound: _____
Tire Temp: _____
Tire additive: MR
Treated Area

SHOCKS	
	Hole Size: F 1.2mm R 1.1mm Holes In Piston: F 2 R 2 Oil wt: F 500 R 500 Springs: F TOP 306 R TOP 306 Rebound: F 20 R 20 Bladder Note: _____ Thread Length: F _____ R _____

ESC
Punch: _____
Initial Brake: _____
Drag Brake: _____
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

FL FR RL RR

BODY	
	Body: PF P37 Wing Height: _____ Wing Position: _____