



SETUP SHEET



**TRACK CONDITIONS**

Type:  Carpet  Asphalt      Size:  Open  Med.  Tight  
 Place:  Indoor  Outdoor      Traction:  High  Med.  Low  
 Surface:  Smooth  Med.  Bumpy      Track Temp/Air Temp: \_\_\_\_\_ / \_\_\_\_\_  
 Note: \_\_\_\_\_

**FRONT SUSPENSION**

Track Width: \_\_\_\_\_ mm       Gear Diff \_\_\_\_\_ wt  
 Toe Angle: **1.5** °       Spool  
 Caster: **4** °  
 Camber: **2** °  
 Ride Height: **5** mm      Anti-Roll Bar: Ø **1.3** mm  
 Down Stop: **5.6** mm

**FF Arm Insert**  
 +0.4 mm  
 +0.2 mm  
 0 mm  
 -0.2 mm  
 -0.4 mm

**FF Arm Mount**  
 #3 (+2 mm)  
 #2 ( 0 mm)  
 #1 (-2 mm)

**FR Arm Mount**  
 Split  
 One Piece  
 #3 (+2 mm)  
 #2 ( 0 mm)  
 #1 (-2 mm)

**FR Arm Insert**  
 +0.4 mm  
 +0.2 mm  
 0 mm  
 -0.2 mm  
 -0.4 mm

Shim: **1** mm  
 Shim: **2.5** mm  
 Hex Adapter: **5**  
 Shim: **0** mm  
 Shim: **2** mm  
 Shim: **4** mm  
 Shim: **0.35** mm  
 Shim: **1** mm  
 Shim: **0.5** mm

Diff.  High  Low

**REAR SUSPENSION**

Track Width: \_\_\_\_\_ mm      Gear Diff **7500** wt  
 Toe Angle: **2.7** °  
 Camber: **2** °  
 Ride Height: **5.2** mm  
 Down Stop: **4.2** mm      Anti-Roll Bar: Ø **1.2** mm

**RF Arm Mount**  
 Split  
 One Piece  
 #3 (+2 mm)  
 #2 ( 0 mm)  
 #1 (-2 mm)

**RF Arm Insert**  
 +0.4 mm  
 +0.2 mm  
 0 mm  
 -0.2 mm  
 -0.4 mm

**RR Arm Mount**  
 #3 (+2 mm)  
 #2 ( 0 mm)  
 #1 (-2 mm)

**RR Arm Insert**  
 +0.4 mm  
 +0.2 mm  
 0 mm  
 -0.2 mm  
 -0.4 mm

Shim: **4** mm  
 Shim: **2** mm  
 Hex Adapter: **5**  
 Shim: **0** mm  
 Shim: **1** mm  
 Shim: **0.25** mm  
 Shim: **2** mm  
 Shim: **0.25** mm

Diff.  High  Low

Chassis:  2.3 mm (kit)  Aluminum

Upper Deck:  1.8 mm  2.0 mm  \_\_\_\_\_ mm (kit)

**ELECTRONICS**

Servo: \_\_\_\_\_  
 ESC: **Nosram hd**  
 Battery: **Lrp 5500**

**DRIVE RATIO**

Spur **110** T  
 Pinion **26** T       $\times 1.9 =$  **8.04**

**MOTOR**

Brand: **Lrp**  
 Turns: **4.53**  
 Timing: \_\_\_\_\_

**TIRES**

Insert: \_\_\_\_\_  
 Wheel: **Team powerg**  
 Shore/deg: \_\_\_\_\_  
 Compound: \_\_\_\_\_  
 Tire Temp: \_\_\_\_\_  
 Tire additive: **Nosram carpet**  
 Treated Area

**ESC**

Punch: \_\_\_\_\_  
 Initial Brake: \_\_\_\_\_  
 Drag Brake: \_\_\_\_\_  
 ESC Timing     Turbo Timing

FL  FR  RL  RR

**SHOCKS**

Hole Size: **F Std** **R Std**  
 Holes In Piston: **F Std** **R Std**  
 Shock Oil WT: **F 500** **R 500**  
 Shock Springs: **F P2.9** **R P2.9**  
 Shock Rebound: **F 0** **R 0**  
 Bladder Note: \_\_\_\_\_  
 Thread Length: **F** **R**  
 Shock Length: **F** **R**

**BODY**

Body Position: **+5mm**      Body: **Protoform type s**  
 Wing Height: **Max**  
 Wing Position: **Max**