

TRACK CONDITIONS			
Type :	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size: <input type="checkbox"/> Open <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Tight
Place :	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction: <input type="checkbox"/> High <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Low
Surface :	<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Med. <input type="checkbox"/> Bumpy	Track Temp/Air Temp: <u>37</u> / <u>27</u>
Note: <u>Track record(new tires)</u>			

FRONT SUSPENSION	
Track Width: _____ mm	<input type="checkbox"/> Gear Diff _____ wt
Toe Angle: <u>1</u> °	<input checked="" type="checkbox"/> Spool
Caster: <u>4</u> °	
Camber: <u>1.5</u> °	
Ride Height: <u>5</u> mm	Anti-Roll Bar: $\varnothing$ <u>1.3</u> mm
Down Stop: <u>5.6</u> mm	

Shim: 1 mm

Shim: 2 mm

Shim: 3 mm

Shim: 0 mm

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 ( 0 mm)
- #1 (-2 mm)

FR Arm Mount

- Split
- One Piece
- #3 (+2 mm)
- #2 ( 0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Shim: 1 mm

Shim: 0.5 mm

Shim: 2 mm

Shim: 0 mm

Diff.

 High  
 Low

Diff.

 High  
 Low

REAR SUSPENSION	
Track Width: _____ mm	Gear Diff <u>8000</u> wt
Toe Angle: <u>2.7</u> °	
Camber: <u>2</u> °	
Ride Height: <u>5.2</u> mm	Anti-Roll Bar: $\varnothing$ <u>1.2</u> mm
Down Stop: <u>4.6</u> mm	

Shim: 4 mm

Shim: 1 mm

Shim: 1.7 mm

Shim: 0.5 mm

RF Arm Mount

- Split
- One Piece
- #3 (+2 mm)
- #2 ( 0 mm)
- #1 (-2 mm)

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RR Arm Mount

- #3 (+2 mm)
- #2 ( 0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Shim: 1 mm

Shim: 0.5 mm

Diff.

 High  
 Low

Diff.

 High  
 Low

None

Chassis:  2.3 mm (kit)  Aluminum

Upper Deck:  1.8 mm  2.0 mm (kit)  \_\_\_\_\_ mm

ELECTRONICS
Servo: _____
ESC: <b>MM Fleta pro</b>
Battery: <b>MM</b>

DRIVE RATIO
Spur <u>100</u> T
Pinion <u>42</u> T $\times 1.9 =$ <u>4.52</u>

SHOCKS
Hole Size: <b>F kit</b> <b>R kit</b>
Holes In Piston: <b>F kit</b> <b>R kit</b>
Shock Oil WT: <b>F 550</b> <b>R 550</b>
Shock Springs: <b>F P2.6</b> <b>R P2.7</b>
Shock Rebound: <b>F 0</b> <b>R 0</b>
Bladder Note: _____
Thread Length: <b>F 9.5mm</b> <b>R 9.5mm</b>
Shock Length: <b>F</b> <b>R</b>

MOTOR
Brand: <b>MM v2</b>
Turns: <u>13.5</u>
Timing: <u>0</u>

TIRES
Insert: <b>Volante</b>
Wheel: <b>Volante</b>
Shore/deg: <u>36</u>
Compound: <b>Volante</b>
Tire Temp: _____
Tire additive: <b>MR33 V3</b>
Treated Area

ESC
Punch: _____
Initial Brake: _____
Drag Brake: _____
<input type="checkbox"/> ESC Timing <input type="checkbox"/> Turbo Timing

FL

FR

RL

RR

BODY	
Body Position: <u>+3</u>	Body: <b>Protoform Type S</b>
Wing Height: _____	Wing Position: _____