

TRACK CONDITIONS			
Type :	<input type="checkbox"/> Carpet	<input checked="" type="checkbox"/> Asphalt	Size: <input checked="" type="checkbox"/> Open <input type="checkbox"/> Med. <input type="checkbox"/> Tight
Place :	<input type="checkbox"/> Indoor	<input checked="" type="checkbox"/> Outdoor	Traction: <input type="checkbox"/> High <input checked="" type="checkbox"/> Med. <input type="checkbox"/> Low
Surface:	<input type="checkbox"/> Smooth <input type="checkbox"/> Med. <input checked="" type="checkbox"/> Bumpy	Track Temp/Air Temp: <u>35</u> / <u>28</u>	
Note: _____			

FRONT SUSPENSION

Track Width: _____ mm Gear Diff _____ wt

Toe Angle: 1 ° Spool

Caster: 4 °

Camber: 1.5 °

Ride Height: 5.2 mm Anti-Roll Bar: \varnothing 1.3 mm

Down Stop: 5.6 mm

FF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

FF Arm Mount

- #3 (+2 mm)
- #2 (0 mm)
- #1 (-2 mm)

FR Arm Mount

- Split
- One Piece
- #3 (+2 mm)
- #2 (0 mm)
- #1 (-2 mm)

FR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Shim: 1 mm Shim: 1.5 mm

Button Screw Grub Screw No Screw

Hex Adapter: kit

Diff. High Low

Shim: 3 mm Shim: 0 mm

Shim: 0 mm Shim: 0 mm

Shim: 1 mm T-Mount Plate Mount

REAR SUSPENSION

Track Width: _____ mm Gear Diff 8000 wt

Toe Angle: 2.7 °

Camber: 2 °

Ride Height: 5.4 mm

Down Stop: 4.4 mm Anti-Roll Bar: \varnothing 1.2 mm

RF Arm Mount

- Split
- One Piece
- #3 (+2 mm)
- #2 (0 mm)
- #1 (-2 mm)

RF Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

RR Arm Mount

- #3 (+2 mm)
- #2 (0 mm)
- #1 (-2 mm)

RR Arm Insert

- +0.4 mm
- +0.2 mm
- 0 mm
- 0.2 mm
- 0.4 mm

Shim: 4 mm Shim: 2 mm

Button Screw Grub Screw No Screw

Hex Adapter: kit

Diff. High Low

Shim: 0.7 mm Shim: 2 mm

Shim: 0.5 mm Shim: 0.5 mm

None

Chassis: 2.3 mm (kit) Aluminum

Upper Deck: 1.8 mm 2.0 mm (kit) _____ mm

3D Flex Damper Tube

ELECTRONICS

Servo: SRT

ESC: MM Pro

Battery: Corally 8000

DRIVE RATIO

Spur 100 T

Pinion 30 T $\times 1.9 =$ 6.33

MOTOR

Brand: MM v2

Turns: 13.5t

Timing: 0

TIRES

Insert: volante

Wheel: volante

Shore/deg: 36

Compound: volante

Tire Temp: _____

Tire additive: MR33 v3

Treated Area

ESC

Punch: max

Initial Brake: _____

Drag Brake: 6

ESC Timing Turbo Timing

FL FR RL RR

SHOCKS

Hole Size: **F** kit **R** kit

Holes In Piston: **F** kit **R** kit

Shock Oil WT: **F** 500 **R** 500

Shock Springs: **F** P2.6 **R** L2.6

Shock Rebound: **F** 0 **R** 0

Bladder Note: _____

Thread Length: **F** _____ **R** _____

Shock Length: **F** 9.5 **R** 9.5

BODY

Body Position: +3

Body: Protoform TYPE S

Wing Height: _____

Wing Position: rear